

宁波金羽桥照明科技有限公司
NINGBO KING-BRIDGE LIGHTING
TECHNOLOGY CO.,LTD.

地址：浙江省余姚市阳明街道新桥工业区
Add: Xinqiao Industry Zone, Yangming Street, Yuyao City,
Zhejiang Province, China
Tel: +86-574-6256 6890
Fax: +86-574-6256 6827
info@kled.com

国内营销中心:

金羽桥照明科技（上海）有限公司
地址：上海市长宁区中山西路179号4K室
电话：189 1897 7928

KLED
— King-Bridge Lighting —

Linear Lighting
Inground Lighting
Inwater Lighting



KLED.com



Linear Lighting

Architectural landscape lighting fixtures achieve a comfortable environmental image through wall lighting. The optics and control are very simple, and it have the function of RGBW full-color and color temperature changed.

P6	L-02
P10	L-05
P14	L-09

Overview Linear Lighting



L-02
P6
NEW

L-05
P10
NEW

	L-02 P6 NEW	L-05 P10 NEW
Power	12-60W	7-18W
Light flux LM	1140→5700	665→1710
Colour temperature K	2700 / 3000 / 4000	2700 / 3000 / 4000
RGBW	●	●
Tunable white 2700K-6000K	●	●
DALI	●	-
DMX	●	●
Lengths (range cm)	326→1470	430→950
Ceiling-mounted	●	●
Wall-mounted	●	●



L-02 Series



单色白光
Monochromatic White: DMX




RGB变色
RGB: DMX



RGBW变色
RGBW: DMX

简述 Description



- 挤出铝型材灯体，铝压铸端盖配高温硅胶密封条
- 超白丝印钢化玻璃，具有高视觉舒适性和均匀配光
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达1000小时以上
- 可在地板、墙壁和天花板进行嵌入式安装
- 多种光学组件可选，适用于不同要求照明场合
- 灯具表面最高温度不超过50°C，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

功率: 12W / 36W / 60W
光效: 90-100 Lm/W (Ra80)
色温: 2700K / 3000K / 4000K
输入电压: AC 110V-277V
功能选项: Switch / DMX

- Extruded aluminium body and flush end cover in die-casting complete with silicone gaskets.
- Super white tempered glass, with high visual comfort and uniform lighting distribution.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- Wall and ceiling mount as well as support with adjustable arms.
- Multiple optics be options, suitable for lighting requirements in different applications.
- The maximum surface temperature of all contact temperature <50°C for safety and reliable.
- All external screw are made of 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.


Power: 12W / 36W / 60W
Nominal efficacy: 90-100 Lm/W (Ra80)
CCT: 2700K / 3000K / 4000K
Input voltage: AC 110V-277V
Options: Switch / DMX

- 应用场合: 广场、建筑物、雕塑、标志物、广告牌等景观照明场所
- Applications: For landscape lighting places such as square, buildings, sculptures, signs and billboards.

规格选项 Flexibility

此洗墙灯有三个主要尺寸规格，包括单色白光和彩色混光（RGB，RGBW），对于相同长度的灯具，可灵活选择不同光学配件，为每个照明设计方案提供优异的性能和最大的灵活性

This kind of linear is available in 3 main lengths with LED monochrome white and colour light, and each linear has some optics options for wall washing, it provide exceptional performance and maximum flexibility for every lighting design solution.



L=326mm / P=12W



L=950mm / P=36W




L=1470mm / P=60W

连接方式 Simplified wiring


每个灯具出线两端配有快速连接器，安装连接灯具非常快速方便，不用打开灯具接线，提升了操作安全性

Each linear with two cables complete with quick-coupling (male / femal) connector, so during these mounting operations, the luminaire is never opened, significantly reducing installation times and cost and at the same time increasing operator safety.



* 单个灯具连接的距离超出允许的标准尺寸，需要单独订购连接件


* When installing individual modules, the distance between them can be increased using special accessories (multicore cable and connectors).




安装应用 Applications

在多种的安装环境中有不同的安装方案以适应建筑照明需求


For different installation system in a broad variety of applications in every architectural context.



顶装
Ceiling-mounted




可调节壁挂式
Wall-mounted with adjustable arms



可调节壁挂式
Wall-mounted with adjustable arms

发光角度 Optics



技术参数 Technology data



L-02XL

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535 L-02LED60-28L150	60W	28	Switch / DMX	110-277V	TL14	1535*235*255/4pcs	19
LED chips - RGBW L-02LED60-28RGBWL150	60W	28	DMX	110-277V	TL14	1535*235*255/4pcs	19.5




L-02L

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535 L-02LED36-18L100	36W	18	Switch / DMX	110-277V	TL14	1015*235*255/4pcs	14
LED chips - RGB L-02LED36-18RGBL100	36W	18	DMX	110-277V	TL14	1015*235*255/4pcs	14.5
LED chips - RGBW L-02LED36-18RGBWL100	36W	18	DMX	110-277V	TL14	1015*235*255/4pcs	14.5



L-02S

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535 L-02LED12-6L32	12W	6	Switch / DMX	110-277V	TL14	375*220*260/4pcs	6.9
LED chips - RGB L-02LED12-6RGBL32	12W	6	DMX	110-277V	TL14	375*220*260/4pcs	7.3
LED chips - RGBW L-02LED12-6RGBWL32	12W	6	DMX	110-277V	TL14	375*220*260/4pcs	7.3



可选配件 Accessories options

	Code
安装支架 Bracket	210004913
快插接头公 Quick Male Connector	320000792
快插接头母 Quick Female Connector	320000793



单色白光
Monochromatic White: DMX



RGB变色
RGB: DMX



RGBW变色
RGBW: DMX

简述 Description



- 挤出铝型材灯体，铝压铸端盖配高温硅胶密封条
- 超白丝印钢化玻璃，具有高视觉舒适性和均匀配光
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达1000小时以上
- 可在地板、墙壁和天花板进行嵌入式安装
- 多种光学组件可选，适用于不同要求照明场合
- 灯具表面最高温度不超过50°C，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

功率: 7W / 12W / 18W
光效: 90-100 Lm/W (Ra80)
色温: 2700K / 3000K / 4000K
输入电压: DC 24V
功能选项: Switch / DMX

- Extruded aluminium body and flush end cover in die-casting complete with silicone gaskets.
- Super white tempered glass, with high visual comfort and uniform lighting distribution.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- Wall and ceiling mount as well as support with adjustable arms.
- Multiple optics be options, suitable for lighting requirements in different applications.
- The maximum surface temperature of all contact temperature <50°C for safety and reliable.
- All external screw are made of 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.

Power: 7W / 12W / 18W
Nominal efficacy: 90-100 Lm/W (Ra80)
CCT: 2700K / 3000K / 4000K
Input voltage: DC 24V
Options: Switch / DMX

- **应用场合:** 广场、建筑物、雕塑、标志物、广告牌等景观照明场所
- **Applications:** For landscape lighting places such as square, buildings, sculptures, signs and billboards.

规格选项 Flexibility

此洗墙灯有三个主要尺寸规格，包括单色白光和彩色混光（RGB，RGBW），对于相同长度的灯具，可灵活选择不同光学配件，为每个照明设计方案提供优异的性能和最大的灵活性

This kind of linear is available in 3 main lengths with LED monochrome white and colour light, and each linear has some optics options for wall washing, it provide exceptional performance and maximum flexibility for every lighting design solution.



L=430mm / P=8W



L=638mm / P=12W



L=950mm / P=18W

工作电压 Working voltage

单色线条灯都配有稳压专用电路，即使输入电压在16V-30V之间变化也能保证灯具正常工作

The monochrome linear is fitted with an exclusive electronic circuit which guarantees constant emissions in the input voltage from 16V to 30V.

Constant luminous flux emitted on the entire line (DC 24V)




* 每个串接回路上灯具连接数量不能超过30米

* The number of linear connected on each series circuit shall not up to 30m.


安装应用 Applications

在多种的安装环境中有不同的安装方案以适应建筑照明需求


For different installation system in a broad variety of applications in every architectural context.



顶装
Ceiling-mounted




可调节壁挂式
Wall-mounted with adjustable arms



可调节壁挂式
Wall-mounted with adjustable arms

发光角度 Optics



技术参数 Technology data



L-05L

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/3030 L-05LED18-18L100	18W	18	Switch / DMX	DC 24V	TL14	1000*210*185/4pcs	8.5
LED chips - RGB L-05LED18-18RGBL100	18W	18	DMX	DC 24V	TL14	1000*210*185/4pcs	8.8
LED chips - RGBW L-05LED18-18RGBWL100	18W	18	DMX	DC 24V	TL14	1000*210*185/4pcs	8.8




L-05M

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/3030 L-05LED12-12L65	12W	12	Switch / DMX	DC 24V	TL14	688*210*185/4pcs	6.5
LED chips - RGB L-05LED12-12RGBL65	12W	12	DMX	DC 24V	TL14	688*210*185/4pcs	6.8
LED chips - RGBW L-05LED12-12RGBWL65	12W	12	DMX	DC 24V	TL14	688*210*185/4pcs	6.8



L-05S

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/3030 L-05LED8-8L45	8W	8	Switch / DMX	DC 24V	TL14	480*210*185/4pcs	4.5
LED chips - RGBW L-05LED8-8RGBWL45	8W	8	DMX	DC 24V	TL14	480*210*185/4pcs	4.8



可选配件 Accessories options

	Code
安装支架 Bracket	210004912
快插接头公 Quick Male Connector	320000542
快插接头母 Quick Female Connector	320000543



L-09 Series




单色白光
Monochromatic White: DMX



RGBW变色
RGBW: DMX

简述 Description



- 挤出铝型材灯体，铝压铸端盖配高温硅胶密封条
- 超白丝印钢化玻璃，具有高视觉舒适性和均匀配光
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达1000小时以上
- 可在地板、墙壁和天花板进行嵌入式安装
- 多种光学组件可选，适用于不同要求照明场合
- 灯具表面最高温度不超过50°C，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

功率: 30W / 75W / 100W
光效: 100-110 Lm/W (Ra80)
色温: 2700K / 3000K / 4000K
输入电压: AC220V-240V
功能选项: Switch / DMX

- Extruded aluminium body and flush end cover in die-casting complete with silicone gaskets.
- Super white tempered glass, with high visual comfort and uniform lighting distribution.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- Wall and ceiling mount as well as support with adjustable arms.
- Multiple optics be options, suitable for lighting requirements in different applications.
- The maximum surface temperature of all contact temperature <50°C for safety and reliable.
- All external screw are made of 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.

Power: 30W / 75W / 100W
Nominal efficacy: 100-110 Lm/W (Ra80)
CCT: 2700K / 3000K / 4000K
Input voltage: AC220V-240V
Options: Switch / DMX

- 应用场合: 广场、建筑物、雕塑、标志物、广告牌等景观照明场所
- Applications: For landscape lighting places such as square, buildings, sculptures, signs and billboards.

规格选项 Flexibility

此洗墙灯有三个主要尺寸规格，包括单色白光和彩色混光（RGB，RGBW），对于相同长度的灯具，可灵活选择不同光学配件，为每个照明设计方案提供优异的性能和最大的灵活性

This kind of linear is available in 3 main lengths with LED monochrome white and colour light, and each linear has some optical options for wall washing, it provide exceptional performance and maximum flexibility for every lighting design solution.



L=570mm / P=30W



L=1060mm / P=75W



L=1545mm / P=100W

光学选项 Optical accessories

灯具拥有多款光学配件可选用，为视觉舒适性提供最有效的照明解决方案，避免不必要的眩光并减少光污染

The design has a variety of optical accessories to option, providing the most effective lighting solution for visual comfort, avoiding unnecessary glare and reducing light pollution.



Normally Type
装饰板 Decorative plate




"A" Type
蜂窝板 Honeycomb louvre




安装应用 Applications

在多种的安装环境中有不同的安装方案以适应建筑照明需求


For different installation system in a broad variety of applications in every architectural context.



顶装
Ceiling-mounted




可调节壁挂式
Wall-mounted with adjustable arms



可调节壁挂式
Wall-mounted with adjustable arms


出光效果 Lighting effects



连接方式 Simplified wiring

每个灯具出线两端配用快速连接器，安装连接灯具非常快速方便

Each linear with two cables complete with quick-coupling (male / femal) connector, so during these mounting operations.



* 单个灯具连接的距离超出允许的标准尺寸，需要单独订购连接件

* When installing individual modules, the distance between them can be increased using special accessories (multicore cable and connectors).

技术参数 Technology data



L-09XL

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/5050							
L-09LED100-36L150	100W	36	Switch / DMX	220-240V	TS4/TS15/TS40/TS60	1580*300*120/2pcs	17/2pcs
L-09ALED100-36L150	100W	36	Switch / DMX	220-240V	TS4/TS15/TS40/TS60	1580*300*120/2pcs	17/2pcs
LED chips - RGBW							
L-09LED100-36RGBWL150	100W	36	DMX	220-240V	TE13	1580*300*120/2pcs	17/2pcs




L-09L

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/5050							
L-09LED75-24L100	75W	24	Switch / DMX	220-240V	TS4/TS15/TS40/TS60	1080*235*255/4pcs	23/4pcs
L-09ALED75-24L100	75W	24	Switch / DMX	220-240V	TS4/TS15/TS40/TS60	1080*235*255/4pcs	23/4pcs
LED chips - RGBW							
L-09LED75-24RGBWL100	75W	24	DMX	220-240V	TE13	1070*300*220/4pcs	23/4pcs



L-09S

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/5050							
L-09LED30-12L55	30W	12	Switch / DMX	220-240V	TS4/TS15/TS40/TS60	590*235*255/4pcs	13.5/4pcs
L-09ALED30-12L55	30W	12	Switch / DMX	220-240V	TS4/TS15/TS40/TS60	590*235*255/4pcs	13.5/4pcs
LED chips - RGBW							
L-09LED30-12RGBWL55	30W	12	DMX	220-240V	TE13	590*235*255/4pcs	13.5/4pcs



可选配件 Accessories options

	Code
快插接头公	Quick Male Connector 320000542
快插接头母	Quick Female Connector 320000543



Inground / Inwater Lighting

Recessed luminaire, a variety of optical accessories can be selected to ensure high visual effect comfort, Dimming color control, high strength pressure body and high corrosion resistance

Inground Lighting

P22	M-09
P26	M-211
P30	M-212
P34	M-213
P38	M-214
P42	M-215
P46	M-01
P48	M-16A
P50	M-02
P54	M-03
P54	M-04
P54	M-05
P54	M-06
P54	M-07

Inwater Lighting

P60	N-01
P60	N-02
P60	N-03



M-09
P22
NEW



M-211
P26
NEW



M-212
P30
NEW



M-213
P34
NEW



M-214
P38
NEW



M-215
P42
NEW



M-01
P46



M-16A
P48



M-02
P50
NEW



Ø120
M-03
P54
NEW



Ø150
M-04
P54
NEW

Power	30-100W	7-21W	9-23W	10W	6W		4-6W	1-2W	4W	40-60W	3-6W	6-12W
Light flux LM	3300→11000	350→1050	450→1150	800	420		240→360	60→120	240	4000→6000	210→600	420→1200
Colour temperature K	2700 / 3000 / 4000	2700 / 3000 / 4000	2700 / 3000 / 4000	2700 / 3000 / 4000	2700 / 3000 / 4000		2700 / 3000 / 4000	3000 / 4000 / BLUE	3000 / BLUE	3000 / 4000	3000 / 4000	3000 / 4000
DALI	●	-	-	-	-		-	-	-	●	-	-
RGBW	●	●	●	-	-		-	-	-	●	●	●
Floor-mounted	●	●	●	●	●		●	●	●	●	●	●
Ceiling-mounted	●	-	-	●	●		-	-	-	-	-	-
Wall-mounted	-	●	●	-	-		●	●	●	-	●	●
Lengths (range cm)	550→1520	324→1000	400→1000	-	-		-	-	-	-	-	-
Adjustable optic	●	-	-	●	-		-	-	-	●	-	-

Inwater Lighting



Ø180
M-05
P54
NEW



Ø220
M-06
P54
NEW



Ø260
M-07
P54
NEW



N-01
P60



N-02
P60



N-03
P60

Power	12-25W	40W	60W		6W	18W	40W
Light flux LM	840→2500	4000	6000		600	1800	4000
Colour temperature K	3000 / 4000	3000 / 4000	3000 / 4000		3000 / 4000	3000 / 4000	3000 / 4000
DALI	-	-	-		-	-	-
RGBW	●	●	●		●	●	●
Floor-mounted	●	●	●		-	-	-
Ceiling-mounted	-	-	-		-	-	-
Wall-mounted	●	●	●		-	-	-
Lengths (range cm)	-	-	-		-	-	-
Adjustable optic	-	-	-		●	●	●




单色白光
Monochromatic White: DMX



RGBW变色
RGBW: DMX

简述 Description



- 挤出铝型材灯体，铝压铸端盖配高温硅胶密封条
- 304不锈钢装饰面板和预埋件底座，灯具静态可承载超过5000kg
- 超白丝印钢化玻璃，具有高视觉舒适性和均匀配光
- 多种光学组件可选，适用于不同要求照明场合
- 灯具表面最高温度不超过50℃，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

功率: 30W / 75W / 100W
 光效: 100-110 Lm/W (Ra80)
 色温: 2700K / 3000K / 4000K
 输入电压: DC 24V
 功能选项: Switch / DMX

- Extruded aluminium body, die-casting side cover which complete with silicone gaskets.
- 304 stainless steel decorative panel and install housing box, the static load of the luminaire can resistance 5000kg.
- Super white tempered glass, with high visual comfort and uniform lighting distribution.
- Multiple optics be options, suitable for lighting requirements in different applications.
- The maximum surface temperature of all contact temperature <50°C for safety and reliable.
- All external screw are made of 304 stainless steel.
- The luminaire technical characteristics conform to EN60598-1 standards.

Power: 30W / 75W / 100W
 Nominal efficacy: 100-110 Lm/W (Ra80)
 CCT: 2700K / 3000K / 4000K
 Input voltage: DC 24V
 Options: Switch / DMX

- 应用场合: 广场、建筑物、雕塑、标志物、广告牌等景观照明场所
- Applications: For landscape lighting places such as square, buildings, sculptures, signs and billboards.

规格选项 Flexibility

此洗墙灯有三个主要尺寸规格，包括单色白光和彩色混光（RGB，RGBW），对于相同长度的灯具，可灵活选择不同光学配件，为每个照明设计方案提供优异的性能和最大的灵活性

This kind of linear is available in 3 main lengths with LED monochrome white and colour light, and each linear has some optical options for wall washing, it provide exceptional performance and maximum flexibility for every lighting design solution.



L=550mm / P=30W



L=1040mm / P=75W



L=1520mm / P=100W

光学配件 Optical accessories

灯具拥有多款光学配件可选用，为视觉舒适性提供最有效的照明解决方案，避免不必要的眩光并减少光污染

The design has a variety of optical accessories to option, providing the most effective lighting solution for visual comfort, avoiding unnecessary glare and reducing light pollution.



Normally Type
装饰板 Decorative plate




"A" Type
蜂窝板 Honeycomb louvre




安全性能 Safety performance

装在地面或地板的嵌入式灯具符合标准防滑和抗压要求，触碰灯具表面温度控制在安全标准之内

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 5000 Kg in accordance with EN 60598-2-13.



Temperature < 40° C




Diffuser optics versions complete with non-slip glass




Resistance to static load (5000 Kg)

出光效果 Lighting effects




技术参数 Technology data




M-09XL

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/5050							
M-09LED100-27L150	100W	27	Switch / DMX	DC 24V	TS4/TS15/TE13	1545*240*145/2pcs	31
M-09ALED100-27L150	100W	27	Switch / DMX	DC 24V	TS4/TS15/TE13	1545*240*145/2pcs	31
LED chips - RGBW							
M-09LED100-27RGBWL150	100W	27	DMX	DC 24V	TS4/TS15/TE13	1545*240*145/2pcs	31
M-09ALED100-27RGBWL150	100W	27	DMX	DC 24V	TS4/TS15/TE13	1545*240*145/2pcs	31




M-09L

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/5050							
M-09LED75-18L100	75W	18	Switch / DMX	DC 24V	TS4/TS15/TE13	1065*240*145/2pcs	21
M-09ALED75-18L100	75W	18	Switch / DMX	DC 24V	TS4/TS15/TE13	1065*240*145/2pcs	21
LED chips - RGBW							
M-09LED75-18RGBWL100	75W	18	DMX	DC 24V	TS4/TS15/TE13	1065*240*145/2pcs	21
M-09ALED75-18RGBWL100	75W	18	DMX	DC 24V	TS4/TS15/TE13	1065*240*145/2pcs	21



M-09S

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535/5050							
M-09LED30-9L55	30W	9	Switch / DMX	DC 24V	TS4/TS15/TE13	575*270*245/4pcs	22
M-09ALED30-9L55	30W	9	Switch / DMX	DC 24V	TS4/TS15/TE13	575*270*245/4pcs	22
LED chips - RGBW							
M-09LED30-9RGBWL55	30W	9	DMX	DC 24V	TS4/TS15/TE13	575*270*245/4pcs	22
M-09ALED30-9RGBWL55	30W	9	DMX	DC 24V	TS4/TS15/TE13	575*270*245/4pcs	22





M-211 Series



M-211
7W / 14W / 21W



简述 Description



- 铝型材灯头和铝型材预埋件
- 超厚10mm钢化丝印玻璃，静态可承载超过2000kg
- 特殊设计光源发光模式，无任何眩光
- 插入式设计模式，无任何外露灯具安装部件
- 灯具表面耐油、防水设计，使用安全可靠
- 灯具表面最高温度不超过50℃，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

- Aluminum profile lamp holder and aluminum profile embedded parts.
- Tempered glass, crystal clear 10mm, the static load of the luminaire can resistance 2000kg.
- Special good design for high performance optics, optics, and it has high performance optics and anti glare system.
- Snap in installation with no exposed hardware.
- Supplied with oil and water resistant, it is safety and reliable for using.
- The maximum surface temperature of all contact temperature <50°C for safety and reliable.
- All external screw are in 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.

- **应用场合:** 广场、建筑物、雕塑、标志物、广告牌等景观照明场所
- **Applications:** For landscape lighting places such as square, buildings, sculptures, signs and billboards.

功率: 7W / 14W / 21W
光效: 40-50 Lm/W (Ra80)
色温: 2700K / 3000K / 4000K
输入电压: DC 24V
功能选项: Switch / DMX

Power: 7W / 14W / 21W
Nominal efficacy: 40-50 Lm/W (Ra80)
CCT: 2700K / 3000K / 4000K
Input voltage: DC 24V
Options: Switch / DMX

规格选项 Flexibility

此洗墙灯有三个主要尺寸规格，包括单色白光，对于相同长度的灯具，可灵活选择不同光学配件，为每个照明设计方案提供优异的性能和最大的灵活性

This kind of linear is available in 3 main lengths with LED monochrome white, and each linear has some optical options for wall washing, it provide exceptional performance and maximum flexibility for every lighting design solution.



L=324mm / P=7W



L=624mm / P=14W



L=1000mm / P=21W

安全性能 Satety performance

装在地面或地板的嵌入式灯具符合标准防滑和抗压要求，触碰灯具表面温度控制在安全标准之内

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 2000 Kg in accordance with EN 60598-2-13.



Temperature < 40° C



Diffuser optics versions complete with non-slip glass



Resistance to static load (2000 Kg)

出光效果 Lighting effects

灯具采用反射出光和特殊玻璃光学设计，为视觉舒适性提供最有效的照明解决方案，避免不必要的眩光并减少光污染

The product apply with reflect optical and special glass design, providing the most effective lighting solution for visual comfort, avoiding unnecessary glare and reducing light pollution.



技术参数 Technology data



M-211L

Code	Power	LED Qty	Control Options	Voltage	Optical	Packing Size	Weight
LED chips - 3014							
M-211LED21-114L100	21W	114	Switch / DMX	DC 24V	100°	1040*300*260/4pcs	16.4




M-211M

Code	Power	LED Qty	Control Options	Voltage	Optical	Packing Size	Weight
LED chips - 3014							
M-211LED14-72L62	14W	72	Switch / DMX	DC 24V	100°	665*300*260/4pcs	13




M-211S

Code	Power	LED Qty	Control Options	Voltage	Optical	Packing Size	Weight
LED chips - 3014							
M-211LED7-36L32	7W	36	Switch / DMX	DC 24V	100°	365*300*260/4pcs	8.4



安装示意图 Installation





M-212 Series



M-212
9W / 23W



简述 Description



- 铝挤出灯体和304不锈钢预埋件底座
- 超厚20mm夹层玻璃，静态可承载超过2000kg
- 特殊设计光源发光模式，无任何眩光，具有很好的视觉效果和光舒适性
- 插入式设计模式，无任何外露灯具安装部件，灯具可按标准长度连续连接
- 灯具表面耐油、防水设计，使用安全可靠
- 灯具表面最高温度不超过50°C，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

- Aluminum extruded lamp body and 304 stainless steel embedded base.
- Super thick 20mm laminated glass, the static load of the luminaire can resistance 2000kg.
- Special good design for high performance optics, optics, and it has high performance optics and anti glare system.
- Snap in installation with no exposed hardware, and the luminaire can continuous run of standard lengths.
- Supplied with oil and water resistant, it is safety and reliable for using.
- The maximum surface temperature of all contact temperature <50°C for safety and reliable.
- All external screw are in 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.

- **应用场合:** 广场、建筑物、雕塑、标志物、广告牌等景观照明场所


- **Applications:** For landscape lighting places such as square, buildings, sculptures, signs and billboards.

- 功率:** 9W / 23W
- 光效:** 50-65 Lm/W (Ra80)
- 色温:** 2700K / 3000K / 4000K
- 输入电压:** DC 24V
- 功能选项:** Switch / DMX


- Power:** 9W / 23W
- Nominal efficacy:** 50-65 Lm/W (Ra80)
- CCT:** 2700K / 3000K / 4000K
- Input voltage:** DC 24V
- Options:** Switch / DMX

规格选项 Flexibility

此洗墙灯有二个主要尺寸规格，包括单色白光和彩色混光（RGB，RGBW），对于相同长度的灯具，可灵活选择不同光学配件，为每个照明设计方案提供优异的性能和最大的灵活性



L=400mm / P=9W



L=1000mm / P=23W


This kind of linear is available in 3 main lengths with LED monochrome white and colour light, and each linear has some optical options for wall washing, it provide exceptional performance and maximum flexibility for every lighting design solution.

安全性能 Safety performance

装在地面或地板的嵌入式灯具符合标准防滑和抗压要求，触碰灯具表面温度控制在安全标准之内



Temperature < 40° C



Diffuser optics versions complete with non-slip glass



Resistance to static load (2000 Kg)

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 2000 Kg in accordance with EN 60598-2-13.


出光效果 Lighting effects

灯具采用反射出光和特殊玻璃光学设计，为视觉舒适性提供最有效的照明解决方案，避免不必要的眩光并减少光污染




The product apply with reflect optical and special glass design, providing the most effective lighting solution for visual comfort, avoiding unnecessary glare and reducing light pollution.

技术参数 Technology data




M-212L

Code	Power	LED Qty	Control Options	Voltage	Optical	Packing Size	Weight
LED chips - 2835							
M-212LED23-126L100	23W	126	Switch / DMX	DC 24V	120°	1040*230*135/2pcs	12.6




M-212S

Code	Power	LED Qty	Control Options	Voltage	Optical	Packing Size	Weight
LED chips - 2835							
M-212LED9-49L40	9W	49	Switch / DMX	DC 24V	120°	365*300*260/4pcs	9.6



安装示意图 Installation






M-213



M-213
10W

简述 Description



- 304不锈钢面板和预埋件底座，铝氧化灯体结构
- 超厚15mm钢化丝印玻璃，静态可承载超过5000kg
- 灯具模组投射角度可调，具有很好的光学视觉效果
- 插入式设计模式，无任何外露灯具安装部件
- 灯具表面耐油、防水设计，使用安全可靠
- 灯具表面最高温度不超过50℃，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

- Stainless steel type 304 body and installation housing, Pure aluminium construction fixture body.
- Clear tempered glass 15 mm, the static load of the luminaire can resistance 5000kg.
- The lighting module has tilt adjustable system, and it has high performance optics.
- Snap in installation with no exposed hardware, and the luminaire can continuous run of standard lengths.
- Supplied with oil and water resistant, it is safety and reliable for using.
- The maximum surface temperature of all contact temperature <50°C for safety and reliable.
- All external screw are made of 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.

功率: 10W
 光效: 70-85 Lm/W (Ra80)
 色温: 2700K / 3000K / 4000K
 输入电压: DC 24V
 功能选项: Switch


Power: 10W
 Nominal efficacy: 70-85 Lm/W (Ra80)
 CCT: 2700K / 3000K / 4000K
 Input voltage: DC 24V
 Options: Switch

- 应用场合: 广场、建筑物、雕塑、标志物、广告牌等景观照明场所
- Applications: For landscape lighting places such as square, buildings, sculptures, signs and billboards.

安装应用 Installation

灯具可适用于地板、墙面、地面和吸顶多种安装场地应用

Installation in floor / wall / ground / ceiling,
Multiple applications for formal continuity.



安全性能 Safety performance

装在地面或地板的嵌入式灯具符合标准防滑和抗压要求，触碰灯具表面温度控制在安全标准之内

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 5000 Kg in accordance with EN 60598-2-13.



Temperature < 40° C



Diffuser optics versions complete with non-slip glass




Resistance to static load (5000 Kg)

出光效果 Lighting effects

灯具采用特殊光学设计，为视觉舒适性提供最有效的照明解决方案，避免不必要的眩光并减少光污染，出光角度可调

The product apply with special design, providing the most effective lighting solution for visual comfort, avoiding unnecessary glare and reducing light pollution, the light direction adjustable.




技术参数 Technology data




M-213

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
M-213LED10-1	10W	1	Switch	DC 24V	30°	415*275*275/12pcs	21.6



安装示意图 Installation





M-214
6W

简述 Description



- 304不锈钢面板，ABS和不锈钢组成的安装底座
- 超厚15mm钢化丝印玻璃，静态可承载超过5000kg
- 特殊设计的光学组件，无任何眩光，具有很好的光学视觉效果
- 插入式安装设计模式，无任何外露灯具安装部件
- 灯具表面耐油、防水设计，使用安全可靠
- 灯具表面最高温度不超过50℃，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

功率: 6W
 光效: 70-85 Lm/W (Ra80)
 色温: 2700K / 3000K / 4000K
 输入电压: DC 24V
 功能选项: Switch

- Stainless steel type 304 body, ABS / Stainless steel type 304 installation housing.
- Clear tempered glass 15 mm, the static load of the luminaire can resistance 5000kg.
- Special good design for high performance optics, optics, and it has high performance optics and anti glare system.
- Snap in installation with no exposed hardware, and the luminaire can continuous run of standard lengths.
- Supplied with oil and water resistant, it is safety and reliable for using.
- The maximum surface temperature of all contact temperature <50℃ for safety and reliable.
- All external screw are made of 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.

Power: 6W
 Nominal efficacy: 70-85 Lm/W (Ra80)
 CCT: 2700K / 3000K / 4000K
 Input voltage: DC 24V
 Options: Switch

- 应用场合: 广场、建筑物、雕塑、标志物、广告牌等景观照明场所
- Applications: For landscape lighting places such as square, buildings, sculptures, signs and billboards.

材质 Materials

高品质的材质选择，确保高品质的产品质量，高强度钢化玻璃面板，确保IK10，不锈钢预埋件底座，特殊设计的光学反光杯，使得灯具具有高性能的参数水平

We select materials of highest possible quality, to ensure high-degree product quality. High sturdy tempered glass with protection up to IK10, 304 stainless steel installation housing, special design reflector to keep the fixture higher performance levels.



安全性能 Satety performance

装在地面或地板的嵌入式灯具符合标准防滑和抗压要求，触碰灯具表面温度控制在安全标准之内

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 5000 Kg in accordance with EN 60598-2-13.



Temperature < 40° C

Diffuser optics versions complete with non-slip glass



Resistance to static load (5000 Kg)

Installed flush with floor


出光效果 Lighting effects

灯具采用特殊光学设计，为视觉舒适性提供最有效的照明解决方案，避免不必要的眩光并减少光污染

The product apply with special design, providing the most effective lighting solution for visual comfort, avoiding unnecessary glare and reducing light pollution.



技术参数 Technology data




M-214

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
M-214LED6-2	6W	2	Switch	DC 24V	30°x45° Tilt 15°	475*240*155/8pcs	12.1

LED chips - 3535

安装示意图 Installation





简述 Description



- 304不锈钢面板和预埋件底座，氧化纯铝灯体结构
- 超厚10mm钢化丝印玻璃，静态可承载超过2000kg
- 特殊设计的光学组件，无任何眩光，具有很好的光学视觉效果
- 插入式设计模式，无任何外露灯具安装部件
- 灯具表面耐油、防水设计，使用安全可靠
- 灯具表面最高温度不超过50℃，安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求

功率: 6W / 6W / 4W
 光效: 50-60 Lm/W (Ra80)
 色温: 2700K / 3000K / 4000K
 输入电压: DC 24V
 功能选项: Switch

- Stainless steel type 304 body and installation housing, Pure aluminium construction fixture body.
- Clear tempered glass 10 mm, the static load of the luminaire can resistance 2000kg.
- Special good design for high performance optics, optics, and it has high performance optics and anti glare system.
- Snap in installation with no exposed hardware, and the luminaire can continuous run of standard lengths.
- Supplied with oil and water resistant, it is safety and reliable for using.
- The maximum surface temperature of all contact temperature <50℃ for safety and reliable.
- All external screw are made of 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.


Power: 6W / 6W / 4W
 Nominal efficacy: 50-60 Lm/W (Ra80)
 CCT: 2700K / 3000K / 4000K
 Input voltage: DC 24V
 Options: Switch

- 应用场合: 广场、建筑物、雕塑、标志物、广告牌等景观照明场所
- Applications: For landscape lighting places such as square, buildings, sculptures, signs and billboards.

安装应用 Installation

灯具可适用于地板、墙面、地面和吸顶多种安装场地应用

Installation in floor / wall / ground / ceiling,
Multiple applications for formal continuity.



材质 Materials

高品质的材质选择，确保高品质的产品质量，高强度钢化玻璃面板，确保IK10，PP预埋件底座，特殊设计的光学反光杯，使得灯具具有高性能的光学参数

We select materials of highest possible quality, to ensure high-degree product quality. High sturdy tempered glass with protection up to IK10, PP plastic installation housing, special design optics to keep the fixture higher performance levels.



安全性能 Safety performance

装在地面或地板的嵌入式灯具符合标准防滑和抗压要求，触碰灯具表面温度控制在安全标准之内

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 2000 Kg in accordance with EN 60598-2-13.



Temperature < 40° C



Diffuser optics versions complete with non-slip glass



Resistance to static load (2000 Kg)


光学选项 Optical options

灯具拥有多款光学选项，为视觉舒适性提供最有效的照明解决方案，避免不必要的眩光并减少光污染，并满足不同场所需求应用

The design has a variety of optical accessories to option, providing the most effective lighting solution for visual comfort, avoiding unnecessary glare and reducing light pollution, it can meet the needs of different applications.



Wall washer
M-215A



α 30°x45°



Beam lens
M-215B



α 15°
30°
50°




Diffuser optic
M-215C




α 120°

技术参数 Technology data




M-215A

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
M-215ALED6-1	6W	1	Switch	DC 24V	30°x45° Tilt 15°	320°320°275/8pcs	7.2



M-215B


Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
M-215BLED6-1	6W	1	Switch	DC 24V	15°/30°/50°	320°320°275/8pcs	7.2




M-215C

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
M-215CLE4-1	4W	1	Switch	DC 24V	120°	320°320°275/8pcs	7.2

安装示意图 Installation






M-01A
2W



M-01B
1W

简述 Description



- 铝压铸灯体外壳，高强度透明PC扩散罩
- 侧向单侧发光和双侧发光方式，具有高视觉舒适性和防眩效果
- 耐高温防水硅胶圈、耐腐蚀PP塑料埋件
- 根据需要地板 / 地面 / 墙面嵌入式安装应用
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 所有外部螺钉均为304不锈钢材质

- Die-casting aluminium body, high quality pc diffuser.
- Side radial light with unilateral & bidirectional emission, it with high visual comfort and good anti glare effect.
- High temperature resistant and waterproof silicone rubber ring, corrosion resistant PP plastic installion housing.
- Floor/ground/wall-mounted recessed luminaire intended applications as required.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screw are made of 304 stainless steel.



Ground installation




Floor installation



Wall-mounted installation


光效: 60-70 Lm/W (Ra80)
色温: 3000K / 4000K / BLUE
Nominal efficacy: 60-70 Lm/W (Ra80)
CCT: 3000K / 4000K / BLUE

技术参数 Technology data



M-01A

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 2835 M-01ALED2-8	2W	8	Switch	24V AC/DC	120°	360*245*250/12pcs	6.5



M-01B


Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 2835 M-01BLED1-4	1W	4	Switch	24V AC/DC	120°	360*245*250/12pcs	6.5



M-16A
4W



简述 Description



- 铝压铸灯体外壳，高强度透明玻璃扩散罩
- 侧向发光方式，具有高视觉舒适性和防眩效果
- 耐高温防水硅胶圈、热镀锌安装预埋件
- 根据需要有地板 / 地面 / 墙面嵌入式安装应用
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 所有外部螺钉均为304不锈钢材质

- Die-casting aluminium body, high quality pc diffuser.
- Side radial light with bidirectional emission, it with high visual comfort and good anti glare effect.
- High temperature resistant and waterproof silicone rubber ring, Hot galvanized steel installion housing.
- Floor/ground/wall-mounted recessed luminaire intended applications as required.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screw are made of 304 stainless steel.



Ground installation



Floor installation




Wall-mounted installation

光效: 60-70 Lm/W (Ra80)
 色温: 3000K / BLUE
 Nominal efficacy: 60-70 Lm/W (Ra80)
 CCT: 3000K / BLUE

- 应用场合: 适用于庭院、草地、导向灯等景观照明场所
- Applications: It can be used for landscape lighting places such assuch as courtyard, lawn, guide direction lighting, etc.

技术参数 Technology data



M-16A

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - F5 M-16ALED4-16	4W	16	Switch	24V AC/DC	120°	390*235*200/6pcs	5



M-02
40W / 60W

简述 Description



- 铝压铸灯体外壳，304不锈钢面板
- 10mm厚台阶高强度钢化玻璃，确保过IK10标准测试要求
- 多种光学配件选项，具有高视觉舒适性和防眩效果
- 耐高温防水硅胶圈、耐腐蚀PP塑料埋件
- 根据需要有地板 / 地面嵌入式安装应用，灯具光源模组角度可调
- 无生物蓝光危害风险，符号EN62471: 2008 标准
- 所有外部螺钉均为304不锈钢材质

功率: 40W / 60W
 光效: 90-110 Lm/W (Ra80)
 色温: 3000K / 4000K / RGBW
 输入电压: DC 24V / AC 100-240V
 功能选项: Switch / DMX / DALI

- Die-casting aluminium body, 304 stainless steel fram.
- 10mm higher hardened tempered glass, it ensure pass IK10 standared test.
- Mulpte optics options, it with high visual comfort and good anti glare effect.
- High temperature resistant and waterproof silicone rubber ring, corrosion resistant PP plastic installion housing.
- Floor/ground-mounted recessed luminaire intended applications as required, LED module the angle adjustable.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screw are made of 304 stainless steel.

Power: 40W / 60W
 Nominal efficacy: 90-110 Lm/W (Ra80)
 CCT: 3000K / 4000K / RGBW
 Input volltage: DC 24V / AC 100-240V
 Options: Switch / DMX / DALI


• 应用场合: 适用于庭院、草地、建筑物、雕塑、标志物广告牌等景观照明场所

• Applications: It can be used for landscape lighting places such assuch as courtyard, lawn, buildings, sculptures, signs and billboards etc.


安装应用 Installation

灯具可适用于地板和地面多种安装场地应用


Installation in floor / ground, Multiple applications for formal continuity.



A Indoor floor B Outdoor floor C Ground



Application for wall washer



Application for tree light washer

安全性能 Safety performance

装在地面或地板的嵌入式灯具符合标准防滑和抗压要求，触碰灯具表面温度控制在安全标准之内

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 2000 Kg in accordance with EN 60598-2-13.



Diffuser optics versions complete with non-slip glass



Resistance to static load (5000 Kg)


安装说明 Installation

通过调节底部调节螺钉，来实现灯具模组出光角度，最后达到满足客户照明效果需求


Adjust the bottom adjusting screw to realize the light output angle of the LED module, and finally meet the lighting effect requirements by customer.



发光角度 Optics




技术参数 Technology data



M-02

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535							
M-02LED40-28	40W	28	Switch / DMX / DALI	DC 24V / AC 100-240V	25° / 50°	270*270*295	6
M-02ALED60-28	60W	28	Switch / DMX / DALI	DC 24V / AC 100-240V	25° / 50°	270*270*295	6

安装示意图 Installation





M-03 ~ M-07 Series



Normally Type
Decorative plate



"A" Type
Honeycomb louvre



"B" Type
Diffuser optics



M-03
Ø120 / 3 LEDs



M-03 / 6W



M-03A / 6W



M-03B / 3W

M-04
Ø150 / 6 LEDs



M-04 / 12W



M-04A / 12W



M-04B / 6W

M-05
Ø180 / 12 LEDs



M-05 / 25W



M-05A / 25W



M-05B / 12W

M-06
Ø220 / 18 LEDs



M-06 / 40W



M-06A / 40W

M-07
Ø260 / 25 LEDs




M-07 / 60W



M-07A / 60W

简述 Description



- 铝压铸灯体外壳，304不锈钢面板
- 10mm厚台阶高强度钢化玻璃，确保过IK10标准测试要求
- 多种光学配件选项，具有高视觉舒适性和防眩效果
- 耐高温防水硅胶圈、耐腐蚀PP塑料埋件
- 根据需要要有地板 / 地面 / 墙面嵌入式安装应用
- 无生物蓝光危害风险，符号EN62471: 2008 标准
- 所有外部螺钉均为304不锈钢材质

功率: 3-60W
 光效: 70-100 Lm/W (Ra80)
 色温: 3000K / 4000K / RGBW
 输入电压: DC 24V / AC 100-240V
 功能选项: Switch / DMX

- Die-casting aluminium body, 304 stainless steel fram.
- 10mm higher hardened tempered glass, it ensure pass IK10 standared test.
- Multiple optics options, it with high visual comfort and good anti glare effect.
- High temperature resistant and waterproof silicone rubber ring, corrosion resistant PP plastic installion housing.
- Floor/ground/wall-mounted recessed luminaire intended applications as required.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screw are made of 304 stainless steel.

Power: 3-60W
 Nominal efficacy: 70-100 Lm/W (Ra80)
 CCT: 3000K / 4000K / RGBW
 Input volltage: DC 24V / AC 100-240V
 Options: Switch / DMX

- 应用场合: 适用于庭院、草地、建筑物、雕塑、标志物广告牌等景观照明场所
- Applications: It can be used for landscape lighting places such assuch as courtyard, lawn, buildings, sculptures, signs and billboards etc.

安全性能 Satety performance

装在地面或地板的嵌入式灯具符合标准防滑和抗压要求，触碰灯具表面温度控制在安全标准之内

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 2000 Kg in accordance with EN 60598-2-13.



Temperature < 40° C



Diffuser optics versions complete with non-slip glass




Resistance to static load (5000 Kg)


安装应用 Installation

灯具可适用于地板、墙面和地面多种安装场地应用

Installation in floor / wall / ground, Multiple applications for formal continuity.



A Wall B Indoor floor C Outdoor floor D Ground




Ground installation



Floor installation



Wall-mounted installation



Application for wall washer



Application for tree light


材质 Materials

高品质的材质选择，确保高品质的产品质量，高强度钢化玻璃面板，确保IK10，PP预埋件底座，特殊设计的光学组件，使得灯具具有高性能的光学参数

We select materials of highest possible quality, to ensure high-degree product quality. High sturdy tempered glass with protection up to IK10, PP plastic installation housing, special design optics to keep the fixture higher performance levels.




技术参数 Technology data




M-03

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535							
M-03LED6-3	6W	3	Switch	DC 24V / AC 100-240V	25° / 50°	385*260*125/6pcs	5
M-03LED6-3RGBW	6W	3	DMX	DC 24V / AC 100-240V	25° / 50°	385*260*125/6pcs	5
LED chips - 3535							
M-03ALED6-3	6W	3	Switch	DC 24V / AC 100-240V	25° / 50°	385*260*125/6pcs	5
M-03ALED6-3RGBW	6W	3	DMX	DC 24V / AC 100-240V	25° / 50°	385*260*125/6pcs	5
LED chips - 2835/3030							
M-03BLED3-18	3W	18	Switch	DC 24V / AC 100-240V	120°	385*260*125/6pcs	5
M-03BLED3-3RGBW	3W	3	DMX	DC 24V / AC 100-240V	120°	385*260*125/6pcs	5




M-04

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535							
M-04LED12-6	12W	6	Switch	DC 24V / AC 100-240V	25° / 50°	320*320*150/4pcs	6.1
M-04LED12-6RGBW	12W	6	DMX	DC 24V / AC 100-240V	25° / 50°	320*320*150/4pcs	6.1
LED chips - 3535							
M-04ALED12-6	12W	6	Switch	DC 24V / AC 100-240V	25° / 50°	320*320*150/4pcs	6.1
M-04ALED12-6RGBW	12W	6	DMX	DC 24V / AC 100-240V	25° / 50°	320*320*150/4pcs	6.1
LED chips - 2835/3030							
M-04BLED6-28	6W	28	Switch	DC 24V / AC 100-240V	120°	320*320*150/4pcs	6.1
M-04BLED6-6RGBW	6W	6	DMX	DC 24V / AC 100-240V	120°	320*320*150/4pcs	6.1




M-05

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535							
M-05LED25-12	25W	12	Switch	DC 24V / AC 100-240V	25° / 50°	380*380*165/4pcs	9.4
M-05LED25-12RGBW	25W	12	DMX	DC 24V / AC 100-240V	25° / 50°	380*380*165/4pcs	9.4
LED chips - 3535							
M-05ALED25-12	25W	12	Switch	DC 24V / AC 100-240V	25° / 50°	380*380*165/4pcs	9.4
M-05ALED25-12RGBW	25W	12	DMX	DC 24V / AC 100-240V	25° / 50°	380*380*165/4pcs	9.4
LED chips - 2835/3030							
M-05BLED12-48	12W	48	Switch	DC 24V / AC 100-240V	120°	380*380*165/4pcs	9.4
M-05BLED12-12RGBW	12W	12	DMX	DC 24V / AC 100-240V	120°	380*380*165/4pcs	9.4



M-06


Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535							
M-06LED40-18	40W	18	Switch	DC 24V / AC 100-240V	25° / 50°	460*460*175/4pcs	11
M-06LED40-18RGBW	40W	18	DMX	DC 24V / AC 100-240V	25° / 50°	460*460*175/4pcs	11
LED chips - 3535							
M-06ALED40-18	40W	18	Switch	DC 24V / AC 100-240V	25° / 50°	460*460*175/4pcs	11
M-06ALED40-18RGBW	40W	18	DMX	DC 24V / AC 100-240V	25° / 50°	460*460*175/4pcs	11



M-07

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535							
M-07LED60-28	60W	28	Switch	DC 24V / AC 100-240V	25° / 50°	540*275*170/2pcs	9.8
M-07LED60-28RGBW	60W	28	DMX	DC 24V / AC 100-240V	25° / 50°	540*275*170/2pcs	9.8
LED chips - 3535							
M-07ALED60-28	60W	28	Switch	DC 24V / AC 100-240V	25° / 50°	540*275*170/2pcs	9.8
M-07ALED60-28RGBW	60W	28	DMX	DC 24V / AC 100-240V	25° / 50°	540*275*170/2pcs	9.8

安装示意图 Installation





N-01~N-03
Inwater lighting



N-01
6W




N-02
18W



N-03
40W

简述 Description



- 316不锈钢灯体外壳及面板
- 高强度钢化玻璃，确保过IK08标准测试要求
- 多种光学配件选项，具有高视觉舒适性和防眩效果
- 灯具光源模组角度可调
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 所有外部螺钉均为316不锈钢材质

- 316 stainless steel body and frame.
- Higher hardened tempered glass, it ensure pass IK08 standared test.
- Mutiple optics options, it with high visual comfort and good anti glare effect.
- LED module the angle adjustable.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screw are in 316 stainless steel.


功率: 6W / 18W / 40W
 光效: 90-110 Lm/W
 色温: 3000K / 4000K / RGBW
 输入电压: DC 24V
 功能选项: Switch / DMX

Power: 6W / 18W / 40W
 Nominal efficacy: 90-110 Lm/W
 CCT: 3000K / 4000K / RGBW
 Input volltage: DC 24V
 Options: Switch / DMX

- 应用场合: 水族馆、水池雕塑、广场喷泉、游泳池等场所
- Applications: Aquatic animals exhibition halls, water pool sculptures, fountains, swimming pools etc.




技术参数 Technology data




N-01

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535 N-01LED6-3	6W	3	Switch	DC 24V	25° / 50°	370*250*150/6pcs	7
LED chips - RGBW N-01LED6-3RGBW	6W	3	DMX	DC 24V	25° / 50°	370*250*150/6pcs	7




N-02

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535 N-02LED18-9	18W	9	Switch	DC 24V	25° / 50°	350*300*155/4pcs	10.2
LED chips - RGBW N-02LED18-9RGBW	18W	9	DMX	DC 24V	25° / 50°	350*300*155/4pcs	10.2




N-03

Code	Power	LED Qty	Control Options	Input Voltage	Optics	Packing Size	Weight
LED chips - 3535 N-03LED40-18	40W	18	Switch	DC 24V	25° / 50°	360*180*155/2pcs	6.6
LED chips - RGBW N-03LED40-18RGBW	40W	18	DMX	DC 24V	25° / 50°	360*180*155/2pcs	6.6



发光角度 Optics





L-02

P6

NEW

L-05

P10

NEW

L-09

P14

NEW

Power	12-60W	7-18W	30-100W
Light flux LM	1140→5700	665→1710	3300→11000
Colour temperature K	2700 / 3000 / 4000	2700 / 3000 / 4000	2700 / 3000 / 4000
RGBW	•	•	•
Tunable white 2700K-6000K	•	•	•
DALI	•	-	•
DMX	•	•	•
Lengths (range cm)	326→1470	430→950	560→1530
Ceiling-mounted	•	•	•
Wall-mounted	•	•	•