



The photograph may not match the reference exactly. Please read the product description to identify the finish.

TECHNICAL CHARACTERISTICS



Product Model:	D-20HLED40-16	D-20HLED60-24	D-20HLED80-32	D-20HLED100-48
IP Protection degrees:	IP66			
IK Protection degrees:	IK08			
Light source:	16 x LED CREE / 16 x LUXEON 5050	24 x LED CREE / 24 x LUXEON 5050	32 x LED CREE / 32 x LUXEON 5050	48 x LED CREE / 48 x LUXEON 5050
Total power consumption:	40W	60W	80W	100W
Luminous Flux:	4000-5600Lm	6000-8400Lm	8000-11200Lm	10000-14000Lm
Luminous efficiency:	100-140Lm/w			
Color temperature:	4000K as standard. Optinal 2700K,3000K & 5700K. Amber LED available			
Voltage/Frequency:	110-240V/50-60Hz			
Warranty(Years):	5			
Units per box:	1			
Net Weight(Kg)	11.8	11.8	12	12
Aerodynamic resistance (CxS)	0.245			

MATERIALS / FINISHES

Structure material: High purity aluminium	aiffuser material: Glass
Structure finish: Silver	Diffuser finish: Transparent

GEAR

Multi-voltage electronic gear included (100-240 V / 50-60 Hz)

Lm^(N): Nominal flow of light in actual working conditions. Its actual flow will depend on the environmental conditions and the efficiency of the optics and/or diffuser.

