



X-01 Series
Ceiling lighting



X-01S
12W



X-01M
25W


简述 Description



- 铝压铸灯具底座及散热组件，铝合金拉伸外壳
- 超白丝印钢化玻璃，具有高视觉舒适性和均匀配光，出光角可以选
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可达1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠


- Aluminum die casting base and heatsink, extruded aluminum alloy body.
- Super white screen printing tempered glass. with high visual comfort light distribution, different optical be option.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

技术参数 Technology data



X-01S

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 3535 X-01SLED12-4	12W	4	100V-240V	1050	25°/40°	305*305*280	8



X-01M

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 3535 X-01MLED25-9	25W	9	100V-240V	2150	25°/40°	395*205*320	4