




B-142
12W



B-142S
2.5W/0.1W


简述 Description



- 铝压铸灯体外壳，PC棱纹透明罩，具有高视觉舒适性和均匀配光透镜
- 灯具具有常规供电和太阳能供电2个版本供选择
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达1000小时以上
- 无生物蓝光危害风险，符号EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠

- Die-casting aluminium body, PC prism transparent diffuser with high visual comfort and uniform lighting distribution.
- There are two version design: AC input normally version and solar version.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

技术参数 Technology data



B-142

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 2835							
B-142LED12-60B	12W	60	100V-240V	720	100°	460*260*420	4
B-142SLED3-25B	2.5W/0.1W	25	SOLAR+SENSOR	250	100°	460*260*420	4

延伸产品 More in family



C-142
Bollard Lighting: 12W.
Page. 388



C-142S
Bollard Lighting: 2.5W / 0.1W.
Page. 388