



X-02S1
9W




X-02S
12W



X-02M
25W/36W


简述 Description



- 铝压铸灯具底座及散热组件，快速旋入式安装结构，安装维护非常方便
- 超白钢化玻璃，具有高视觉舒适性和均匀配光
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可达1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008 标准
- 灯具表面最高温度不超过50度，安全可靠


- Aluminum die casting base and heatsink, fast fix structure design, installation and maintenance is very convenient.
- Super white tempered glass. with high visual comfort light distribution.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- The maximum surface temperature of all accessible part under 50 degrees for safety and reliable.

技术参数 Technology data




X-02S1

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - 3030 X-02S1LED9-12B	9W	12	220V~240V	825	80°	200*200*260	8



X-02S

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - COB X-02SLED12-1C	12W	1	220V~240V	1040	80°	285*285*335	8



X-02M

Code	Power	LED Qty	Input Voltage	Lumen	Beam Angle	Packing Size	Pcs/Box
LED chips - COB X-02MLED25-1C	25W	1	220V~240V	2250	90°	380*195*350	4
X-02MLED36-1C	36W	1	220V~240V	3060	90°	380*195*350	4