



F-03 Series




F-03SX  
60-120W



F-03MX  
150-240W

简述 Description



- 铝压铸灯体外壳，超白钢化玻璃，特殊外形设计，有2种尺寸供选择
- 高透光PC透镜，多种光学组件可选，具有高视觉舒适性和防眩效果
- 高性能LED芯片，有ON-OFF / DALI多种控制程序选项
- 灯具具有不同支架选项，可根据需要选配适用在不同场所
- 防紫外线聚氨酯塑粉喷涂表面，耐腐蚀可以达1000小时以上
- 无生物蓝光危害风险，符合EN62471: 2008标准
- 所有外部螺钉均为304不锈钢材质

- Die-casting aluminium body, super white tempered glass. Special shape design, it has 2 sizes version options.
- Optics with PC lens with high visual comfortable and good anti glare effect, multiple light distribution options.
- High quality LED chips, with ON-OFF/DALI programmed options.
- The luminaire have multiple brackets to option, it can suit different application.
- Surface anti-ultraviolet pure polyester powder painting, Corrosion resistance can be more than 1000 hours.
- No photo-biological risk, in accordance with EN 62471:2008.
- All external screws are made of 304 stainless steel.

功率: 60W-240W  
 光效: 120-155 Lm/W  
 色温: 3000K / 4000K / 5000K  
 显色指数: >80Ra / 90Ra  
 功能选项: ON-OFF / DALI

Power: 60W-240W  
 Nominal efficacy: 120-155 Lm/W  
 CCT: 3000K / 4000K / 5000K  
 CRI: >80Ra / 90Ra  
 Options: ON-OFF / DALI

- 应用场合: 车间, 库房, 展览馆等场所等照明场所
- Applications: Workshop, warehouse, exhibition hall, etc.




技术参数 Technology data



**F-03MX**

Code	Power	LED Qty	Optics	Packing Size	Weight	Pcs/20"	Pcs/40"
LED chips - 3535/5050							
<b>F-03MXLED150-64</b>	150W	<b>64</b>	T25/T60/T90/T1	455*455*200	9.0	660	1430
<b>F-03MXLED200-64</b>	200W	<b>64</b>	T25/T60/T90/T1	455*455*200	9.3	660	1430
<b>F-03MXLED240-96</b>	240W	<b>96</b>	T25D/T60D/T90D/T1D	455*455*200	9.3	660	1430



**F-03SX**

Code	Power	LED Qty	Optics	Packing Size	Weight	Pcs/20"	Pcs/40"
LED chips - 3535/5050							
<b>F-03SXLED60-36</b>	60W	<b>36</b>	T60/T90/T1	360*360*200	6.0	1056	2112
<b>F-03SXLED75-36</b>	75W	<b>36</b>	T60/T90/T1	360*360*200	6.0	1056	2112
<b>F-03SXLED100-36</b>	100W	<b>36</b>	T60/T90/T1	360*360*200	6.0	1056	2112
<b>F-03SXLED120-54</b>	120W	<b>54</b>	T60D/T90D/T1D	360*360*200	6.3	1056	2112

