



The photograph may not match the reference exactly. Please read the product description to identify the finish.

TECHNICAL CHARACTERISTICS



Product Model:	T-190CLED40-32	T-190CLED60-32	T-190CLED60-112B
IP Protection degrees:	IP66		
IK Protection degrees:	IK08		
Light source:	32 x LED CREE / 32 x LUXEON 5050	32 x LED CREE / 32 x LUXEON 5050	112 x LUXEON 3030
Total power consumption:	40W	60W	40W
Luminous Flux:	4800-6000Lm	7050-8730Lm	5000Lm
Luminous efficiency:	110-150Lm/w		
Color temperature:	4000K as standard. Optimal 2700K, 3000K & 5700K. Amber LED available		
Voltage/Frequency:	100-240V/50-60Hz		
Warranty(Years):	5		
Units per box:	1		
Net Weight(Kg)	8.4	8.4	8.4

MATERIALS / FINISHES

Structure material: High purity aluminium	aiffuser material: Glass
Structure finish: Silver	Diffuser finish: Transparent

GEAR

Multi-voltage electronic gear included (110-240 V / 50-60 Hz)

Lm^(N): Nominal flow of light in actual working conditions. Its actual flow will depend on the environmental conditions and the efficiency of the optics and/or diffuser.

OUTDOOR

