



简述 Description



- 铝型材灯头和铝型材预埋件
- 超厚10mm钢化丝印玻璃,静态可承载超过2000kg
- 特殊设计光源发光模式,无任何眩光
- 插入式安装设计模式,无任何外露灯具安装部件
- 灯具表面耐油、防水设计,使用安全可靠
- 灯具表面最高温度不超过50℃,安全可靠
- 所有外部螺钉均为304不锈钢材质
- 灯具符合EN60598-1技术标准要求
- Aluminum profile lamp holder and aluminum profile embedded parts.
- Tempered glass, crystal clear 10mm, the static load of the luminaire can resistance 2000kg. • Special good design for high performance optics, optics, and it has high performance optics and anti glare system.
- Snap in installation with no exposed hardware.
- Supplied with oil and water resistant, it is safety and reliable for using. • The maximum surface temperature of all contact temperature <50°C for safety and reliable.
- All external screw are in 304 stainless steel.
- The luminaire technical characteristics conform to EN 60598-1 standards.

• **应用场合**:广场、建筑物、雕塑、标志物、广告牌等景观照明场所

• Applications: For landscape lighting places such as square, buildings, sculptures, signs and billboards.







功率: 光效: 色温: 输入电压: 功能选项:

7W / 14W / 21W 40-50 Lm/W (Ra80) 2700K / 3000K / 4000K DC 24V Switch / DMX


Power: Nominal efficacy: CCT: Input volltage: Options:

7W / 14W / 21W 40-50 Lm/W (Ra80) 2700K / 3000K / 4000K DC 24V Switch / DMX

规格选项 Flexibility

此洗墙灯有三个主要尺寸规格,包括单色白光, 对于相同长度的灯具,可灵活选择不同光学配 件,为每个照明设计方案提供优异的性能和最 大的灵活性

This kind of linear is available in 3 main lengths with LED monochrome white, and each linear has some optical options for wall washing, it provide exceptional performance and maximum flexibility for every lighting design solution.



L=1000mm / P=21W

安全性能 Satety performance

出光效果 Lighting effects

必要的眩光并减少光污染

装在地面或地板的嵌入式灯具符合标准防滑和 抗压要求,触碰灯具表面温度控制在安全标准 之内

Ground and floor level recessed luminaires, have different degrees of resistance to torsion and shear, up to 2000 Kg in accordance with EN 60598-2-13.

灯具采用反射出光和特殊玻璃光学设计,为视 觉舒适性提供最有效的照明解决方案,避免不

The product apply with reflect optical and special glass design, providing the most effective lighting solution for visual comfort,

avoiding unnecessary glare and reducing light







Diffuser optics versions complete with non-slip glass








Resistance to static load (2000 Kg)



M-211S Code Power LED LED chips - 3014 M-211LED7-36L32 7W 36





pollution.

技术参数 Technology data



M-211L								
Code	Power	LED Qty	Control Options	Voltage	Optical	Packing Size	Weight	
LED chips - 3014								
M-211LED21-114L100	21W	114	Switch / DMX	DC 24V	100°	1040*300*260/4pcs	16.4	



M-211M								
Code	Power	LED Qty	Control Options	Voltage	Optical	Packing Size	Weight	
LED chips - 3014 M-211LED14-72L62	14W	72	Switch / DMX	DC 24V	100°	665*300*260/4pcs	13	



Qty	Control Options Voltage		Optical	Packing Size	Weight
	Switch / DMX	DC 24V	100°	365*300*260/4pcs	8.4

安装示意图 Installation

